


High-Quality Optics Fibre Endoscopy



Gastrosopes

Efficient and safe:
The most modern technology with
the highest standard of hygiene.

PENTAX

High-Quality Optics Fibre Gastroscopy



With these fibre gastroscopes, PENTAX offers both doctors with practices and hospitals outstanding optical quality, exemplary ergonomics, innovative design and maximum hygiene standards.

Outstanding performance characteristics



Maximum Working Comfort

- Up to 210° deflection and 125° angle of view for the best possible navigation and viewing even in hard-to-reach areas.
- Optimum dimension of the working channel permit a wide range of therapeutic uses and effective suction.
- Very comfortable and hygienic handling thanks to the optimized positioning of the ocular and suction channel.

Unique Hygiene

- PENTAX CleanCap System*: the highest international hygiene standard thanks to the detachable distal cap for safe and rapid mechanical cleaning of the air and water channels.
- High load-bearing capacity of material thanks to PENTAX SafetySeal.

Excellent picture quality

- High-Quality Optics system for extra-wide 125° angle of view.
- PENTAX Superfine Fibre Technology gives the highest optical image resolution and high colour discrimination.
- Excellent video imaging and documentation possibilities through simple EFER Mucam video camera connection.

PENTAX Quality & Service Programme

- Exceptional quality and longevity.
- Innovative detail solutions for more convenience and safety.
- All-round 100% service plan: consulting, financing, technical service, training.
- PENTAX fibre gastroscopes are compatible with the EFER Mucam video system, for long-term investment security.

* only for W series

Diagnostic/Therapeutic Fibre Gastroscopes

Type	FG-15W	FG-24W	FG-29W	FG-34W	FG-16V
Angle of view (°)	120	105	100	100	125
Focus (mm)	3-50	3-100	3-100	3-100	3-50
Tip deflection (°) up/down right/left	210/120 120/120	210/120 120/120	210/120 120/120	210/120 120/120	180/180 160/160
Ø Insertion tube (mm)	4.9	7.9	9.8	11.3	5.3
Ø Distal end (mm)	4.9	8.2	10.0	11.5	5.2
Ø Instrument channel (mm)	2.0	2.2	2.8	3.8	2.0
Working length (mm)	1050	1050	1050	1050	925
Total length (mm)	1395	1395	1395	1395	1270

PENTAX Europe GmbH
LIFE CARE
Julius-Vosseler-Straße 104
22527 Hamburg
Germany
Tel.: +49 40 / 5 61 92 - 0
Fax: +49 40 / 5 60 42 13
E-mail: medical@pentax.de

PENTAX U.K. Limited
LIFE CARE
Pentax House
Heron Drive, Langley
Slough SL3 8PN
United Kingdom
Tel.: +44 17 53 / 79 27 23
Fax: +44 17 53 / 79 27 94
E-mail: lifecare.info@pentax.co.uk

PENTAX France S.A.S.
LIFE CARE
112 quai de Bezens
P. B. 204
95106 Argenteuil
France
Tel.: +33 1 / 30 25 75 75
Fax: +33 1 / 30 25 75 76
E-mail: medical@pentax.fr

PENTAX Nederland B.V.
LIFE CARE
Lage Mosten 35
4822 NK Breda
Netherlands
Tel.: +31 76 / 5 31 30 31
Fax: +31 76 / 5 31 30 00
E-mail: lifecare@pentax.nl

PENTAX Italia S.r.l.
LIFE CARE
Via Dione Cassio, 15
20138 Milano
Italy
Tel.: +39 / 02 50 99 58 1
Fax: +39 / 02 50 99 58 60
E-mail: marketing.lifecare@pentaxitalia.it

HOYA Corporation
PENTAX Tokyo Office
2-36-9, Maeno-cho
Itabashi-Ku
174-8639 Tokyo
Japan
Tel.: +81 33 / 9 60 51 55
Fax: +81 35 / 3 92 67 24

www.pentaxeurope.com



HOYA Corporation · ISO 9001/EN ISO 13485 certified

Your PENTAX sales representative:

PENTAX